

BID SPECIFICATIONS MID-MOUNT ZTR MOWER

SPECIFICATIONS

Engines – 25 hp Kohler Command SP with electric start, governed to 3750 rpm.

Air Filter – Heavy-duty canister air filtration system.

Drive System – Two Hydro-Gear 12cc variable-displacement pumps with integral relief valves powering two high-torque Hydro-Gear wheel motors with 1.25" diameter tapered shafts. Shaft mounted cooling fan on one pump.

Ground Speed – 0 to 9.5 mph (15.3 kmph) forward, 0 to 6.1 mph (9.8 kmph) reverse, infinitely variable.

Hydro Fluid – Synthetic oil.

Cutting Deck – 10-gauge top that is formed and continuously seam-welded, with 10-gauge top reinforcement plate and 7-gauge side skirt. 7-gauge reinforcement rings at spindle assembly, 5.5" deep, 4-point suspension, full-floating deck with six adjustable, anti-scalp rollers. Deck lift assist standard.

Cutting Height – 1.5" to 5.0" in 0.25" increments. Adjustable from operator's seat.

Drive Tires – 24 x 12-12, 4-ply Turf Master.

Front Caster Tires – 13 x 5.0-6; smooth tread pneumatic.

Casters – Double-yoke, caster wheel assembly.

Steering and Motion Control – Hydraulically dampened twin levers, adjustable fore and aft for smooth and comfortable control. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to two height positions.

Quick-Lift Deck Assist – Standard.

Curb Weight – 1,130 lbs.

Dimensions:

Width

60" Side-Discharge

Deflector Up61.4"

Deflector Down 72.2"

Length

60" Deck 78.5"

Height

(ROPS Up) 72.0"

Blades – 60" deck: 3-20.50" blades

Blade-Tip Speed – Approximately 18,500 fpm.

Blade Spindles – Spindle diameter is 1.75" at blade mounting and 25mm diameter at bearing surface. Mounted in cast aluminum alloy spindle housing with dual sealed high speed ball bearings. No maintenance required.

Tractor Frame – Welded, heavy-duty tubular steel.

Turning Radius – True zero-turn.

Drive-Wheel Release – Allows unit movement without engine running.

Parking Brake – Lever-actuated drum and band integrated with transmission-neutral interlock.

Fuel Capacity – 11.0-gallon, twin fuel tanks.

2008 Bid Specification Sheet

Electrical – 12-volt battery with 15-amp alternator.

PTO Engagement – MagStop electromagnetic 200-ft-lbs clutch with spot brake. 2-year warranty.

Hour Meter – Standard.

Safety Package – Operator Presence Controls (OPC) and drive system interlock.

Seat – High-back, "EVC" (Elastomeric Vibration Control) seat, which has no springs to break, adjusts fore and aft and features padded armrests.

Rollover Protection – Standard with 2-post foldable ROPS. Includes retractable seat belt and seat latch.

Available Accessories and Attachments

Operator Controlled Discharge	OCD01
LazerLocker™ (requires 2 units when UltraVac is installed)	109-5614
UltraVac™ Collection System	UV60/109-1179/103-5633
QDS	UVD60/109-1179/103-5633
Mulching Kits	MK604Q
Turf Striping Kit	STRLZ60
Full-Suspension Seat	LSSEAT
CustomRide Seat Suspension	103-4754
Hitch Kit	1-631665
Sun Shade	FRPSSHADE
Light Kit	FRPSLKIT
Trash Container, 2.5-gallon capacity	TC25
Cup Holder	1-641284

Disregard

2008 Bid Specification Sheet